EZN3260 Plus

2 Megapixel HD Outdoor IR & WDR Bullet Network Camera

NEW

neVio HD Series | ONVIF & PSIA Compliant

2.0 Megapixel | WDR | True Day/Night | 3DNR | IP66 Weather Resistant | IR Max 40m

PoE | Vandal Resistant | micro SDHC card slot | Heater | Motion Detection Support | TWO Way Audio | CE | FC FEDERAL COMMUNICATION COMMISSION U.S.A.

Features

- 1/3" HD color CMOS image sensor delivers high resolution, and supports both H.264 and Motion JPEG in full frame rate
- Supports both H.264 and Motion JPEG in full 30fps frame rate
- High Performance Noise Filter improves image quality
- Wide Dynamic Range
- Dual Codec for H.264 and M-JPEG allows choice of stream formats to fit the application
- Provides true day/night functionality with automatic IR filter operation
- Two Way Audio transport (line level input/output)
- Dual power capability PoE or 12VDC for flexible installation
- Local alarm inputs and outputs
- Extended IR range of up to 40M/131ft. with 44 LEDs
- Split glass to prevent internal IR reflections
- E-Z lock ring at the base is designed with easy to grip tabs for firmly clamp the camera in place, plus a set screw for added security
- Easy bottom access to video test point and lens control inside weatherproof cover plus Remote Zoom & Focus adjustment by web browser
- IP66 and vandal resistant
- Built-in micro SDHC slot for a SDHC card enabling local storage
- ONVIF / PSIA compliance interoperates with a broad range of systems

Dimensions



Specifications

Pickup Device	1/3" HD progressive scan CMOS sensor
Lens	Vari-focal lens, Auto Iris, 2.8-10mm, F1.3, 19Φ
Minimum Illumination	0Lux @ F1.3 (IR on)
Day/Night	True Day/Night with IR cut filter
Shutter Time	1/125~1/60,000sec.
Video Compression	H.264/M-JPEG
Max. Video Resolution	1920 x 1080
Frame Rate	1080P@30fps
Angle of View	Wide: Horizontal 100°, Vertical 73.3°, Diagonal 129.1° Tele: Horizontal 273°, Vertical 20.4°, Diagonal 34.3°
S/N Ratio	>50 db
Privacy Mask	Yes
Region of Interest	Yes
Video Streaming	Multi-stream H.264, and Motion JPEG: 1 stream in max. resolution at 30 fps; more streams if identical or limited in frame rate/resolution
Image Settings	Compression, Brightness, Sharpness, Contrast, Saturation, Hue, White balance, Exposure control, Backlight compensation, Rotation, Mirroring of images, Text and image overlay, Auto Gain Control, Auto White Balance
WDR	Yes
3D Noise	On/Off
Audio Compression	G.711
Operation Mode	Two-way audio
Interface	10Base-T/100Base-TX auto-negotiation, RJ-45 socket Support MDI/MDI-X auto crossover function
Supported Protocols	TCP/IP, IPV6, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, SNMP, FTP, HTTP, HTTPs, PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP, UDP, IGMP, ICMP, ARP, ONVIF, PSIA
Alarm Input/Output	1/1
Event Trigger	Alarm Input, Manual Trigger, Motion Detection, Tamper detection
Notification	Trigger alarm output, Send mail notification, Upload video to FTP, Record video to PC and Network alarm
Micro SD Card	Secure Disk physical layer specification version 2.0 Supports SDHC Host Specification
Power Supply	12 VDC & PoE
Power over Ethernet	PoE 802.3af
Max. Power Consumption	9W (IR LEDs on)
Water Resistant	IP66
Operating Temperature	-40°C~55°C/-40°F~131°F (DC12V) -20°C~55°C/-4°F~131°F (PoE)
Humidity	20%~80% not condensing
Dimensions (O.D.x L) (O.D. x H x L)	(In line) Φ105.5 x 359.9mm/Φ4.15" x 14.17" (Right angle) Φ105.5 x 145 x 312.7mm/Φ4.15" x 5.7" x 12.3"
Weight	1.62 kg/3.57lbs
Certificates	CE, FCC

* All product specifications are subject to change without notice

* Models vary in different countries. Please visit EverFocus regional websites for detailed ordering information

* Lens models and availability vary in different regions